



1 Molten Street, Delville Ext. 4, C

Po Box 23 , Germi

Tel: (011) 8

Fax: (011)

Fax to Email 08

E-mail: jhb@sv

web site www.swifts

PRODUCT DATA

P 3 SAFETY SOLVENT

DESCRIPTION

A non flammable colourless liquid which dries at medium speed without residue. The boiling range is above 120°C.

SOIL REMOVAL AND APPLICATION

- This solvent must be used cold.
- Solvent can be applied by brush, dipped or spray method.
- It is a good solvent for grease, oil, gums and waxes.
- If used in a vapour degreasing tank it must only be used in an approved type tank, designed for higher boiling point chlorinated fluids.

TYPICAL APPLICATIONS

- Rolls
- Bearings
- Fabrics
- Some electrical equipment.

CHECK COMPATIBILITY WITH PLASTIC!!!!!!

COMPOSITION

- Prevent prolonged skin contact by use of mechanical handling devices, protective gloves and skin creams.
- Goggles and / or face shield should be worn.
- Inhalation hazard is high. Unless a specially designed degreasing unit is used, correctly operated and positioned, additional control measures such as exhaust ventilation on immersion tank are necessary.
- If sprayed the sprayer should be equipped with approved respiratory protection.
- There is no fire hazard under normal conditions.
- Welding or flame cutting must not be carried out on tanks containing ethylene tetrachloride.
- It may not be used for cleaning oxygen lines of flame cutting equipment.
- This solvent should never be used near open flames because of the toxicity of decomposition products.

PACKAGING

400 G	1-700 6340
1 L	1-700 6341
5L	1-700 6342
25L	1-700 6343
200L	1-700 6344

Germiston
iston 1400
27-5935
824-2125
66714060
wifts.co.za
s.co.za